

## EARLES LINSEED OIL GLOSS. A BREATHABLE DECORATIVE COATING SUITABLE FOR INTERIOR AND EXTERIOR APPLICATION

### PRODUCT DESCRIPTION

Linseed Oil Gloss is a traditional solvent free oil based paint. Used as a decorative and protective coating for all woodwork giving a water resistant, flexible coating, with high opacity, excellent longevity and easy application. Highly pigmented in 100% Pure Boiled Linseed Oil, with added driers but no solvents, using traditional and modern pigments. Contains a natural biocide additive (mould protection).

### PERFORMANCE

A highly durable coating with a natural gloss finish.

### PRODUCT FEATURES

- Long lasting
- Environmentally friendly
- No harmful fumes in use
- Finish can be maintained with oil every few years
- Breathable
- Plastic, solvent and VOC free
- Weather resistant

### COLOUR RANGE

As per colour card.

### PAINT FINISH

Natural Gloss.

### STORAGE AND SHELF LIFE

12 Months in unopened containers. Store in a dry location in original containers between 5°C and 25°C.

### DRYING TIME

Very slow drying, up to two weeks for full drying, weather dependant.

### OVERCOATING TIME

24 hours minimum.

### THEORETICAL SPREAD RATE

Conservative spread rate of 8m<sup>2</sup>-10m<sup>2</sup> per litre per coat on porous bare substrate, potential spread rate up to 15m<sup>2</sup>-20m<sup>2</sup> per litre per coat.

### COATS

Minimum of 2 coats is required. See application guidelines.

### PACK SIZE

1 litre and 2.5 litre tins

### THINNER

Thinning method 1 - stand the tin of paint in a container of very hot water.

Thinning method 2 - Using Genuine Turpentine. This will reduce the solids content and also introduces flammability.

### APPLICATION METHOD

Brush

### CLEANING

Clean brushes and other painting equipment using a solvent such as genuine turpentine.

### DISPOSAL

Dispose of in accordance with local authority requirements. Do not allow the product to enter watercourses or drains or where ground or surface waters may be affected. All waste material including empty containers are controlled wastes and should be disposed of in accordance with the regulations under The Control Of Pollution Act. Using information provided in this data sheet, advice should be obtained from the waste regulation authority whether any special regulations apply.

### SAFETY PRECAUTIONS

Application materials and soiled rags may self ignite without warning. Dispose of safely by laying flat and allowing to dry or clean with warm soapy water to avoid fire risks.

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- If medical advice is needed, have product container or label at hand.

### PRODUCT ASSISTANCE

Contact Earles Paint:

Email: [enquiries@earlespaint.co.uk](mailto:enquiries@earlespaint.co.uk)

phone: +44(0)1665 494034

[www.earlespaint.co.uk](http://www.earlespaint.co.uk)

Important: The content of this documentation is based on our experience of the product. The company guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application including non-use of the company's approved application tools, application by non-competent personnel, use of products not compatible with the company's products or bad weather conditions. For further information, refer to the material safety data sheet.