

EARLES TRADITIONAL LIMEWASH. A BREATHABLE DECORATIVE COATING SUITABLE FOR BOTH INTERIOR AND EXTERIOR APPLICATION

PRODUCT DESCRIPTION

An internal & external limewash made from pure filtered slaked lime modified with sodium chloride. Limewash in its purest simplest form.

PRODUCT FEATURES

- Highly breathable
- Traditional Lime Finish
- Easy to apply
- No VOC's
- Plastic and solvent free
- Compatible with period properties

COLOUR RANGE

As per colour card

PAINT FINISH

Chalky matt finish with a natural patina

STORAGE AND SHELF LIFE

Store in a dry location in original containers between 5°C and 25°C. Indefinite shelf life in unopened containers.

DRYING TIME

4 hours at 20°C, dependent on airflow and humidity.

OVERCOATING TIME

24 hours

THEORETICAL SPREAD RATE

9m² per litre per coat.
(based on dilution rates and application guidelines)

COATS

Recommended 3 coat system.
(Please read application guidelines)

PACK SIZE

5 and 10 litres

THINNER/CLEANER

Water.

APPLICATION METHOD

Brush (2 knot brush or good masonry brush)

CLEANING

Clean all equipment with fresh water immediately after use.

DISPOSAL

Dispose of in accordance with local authority requirements.

Do not allow the product to enter watercourses or drains or dispose of where ground or surface waters may be affected. All waste material including empty containers are controlled wastes and should be disposed of in accordance with the regulations under The Control Of Pollution Act. Using information provided in this data sheet, advice should be obtained from the waste regulation authority whether the special regulations apply..

SAFETY PRECAUTIONS

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- If medical advice is needed, have product container or label at hand.

RESPIRATORY PROTECTION:	Wear a dust mask.
HAND PROTECTION:	Wear protective gloves.
SKIN PROTECTION:	Cover arms and legs.
EYE PROTECTION:	Wear suitable safety glasses
IF SWALLOWED:	Do not induce vomiting. Seek medical advice if ingested or if an allergic reaction occurs.

PRODUCT ASSISTANCE

Contact Northern Paints and Coatings Ltd:

Email: sales@npc-ltd.co.uk or phone: +44(0)1665 494034

www.npc-ltd.co.uk

Important: The content of this documentation is based on our experience of the product. The company guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application including non-use of the company's approved application tools, application by non-competent personnel, use of products not compatible with the company's products or bad weather conditions. For further information, refer to the material safety data sheet.