

EARLES NATURAL CLAYPAINT. BREATHABLE INTERIOR EMULSION WITH UNMATCHED CHARM AND CHARACTER FOR WALLS AND CEILINGS

PRODUCT DESCRIPTION

Earles Natural Claypaint is based on a traditional Victorian casein resin emulsion using natural clays and added pale boiled linseed oil. A highly breathable paint for interiors and suitable for application to lime plasters.

PRODUCT FEATURES

- Highly breathable
- Can be applied to bare surfaces without priming
- Traditional matt finish with subtle transitions
- Limewash compatible
- Safe to use and non-toxic
- Solvent, plastic and VOC free

COLOUR RANGE

As per colour card.

PAINT FINISH

Traditional soft matt finish

STORAGE AND SHELF LIFE

Store between 5°C and 25°C in a dry location in original airtight containers. **Use within 3 months of purchase.**

DRYING TIME

30 Minutes at 20°C at 60% Relative Humidity

OVERCOATING TIME

2 to 4 hours at 20°C

THEORETICAL SPREAD RATE

10 m² per litre depending upon type of application and surface porosity.

COATS

Recommended 1 priming mist coat followed by 2 full coats. See application guidelines sheet for full application instructions.

PACK SIZE

2.5 and 5 Litre tins

PREPARATION

Ensure surface to be coated is clean, dry and free from any dirt, grease and loose or flaking paint. Existing painted surfaces should be lightly abraded before application.

Earles Hand Crafted Clay Paint should not be applied to lime plastered surfaces under 3 months old.

APPLICATION

New surfaces must be primed with a mist coat using approximately 20% water to volume.

Apply using a good quality brush or medium pile roller, making sure not to apply the paint too thickly.

Apply only when temperatures are above 5°C and the relative humidity is above 65%. To test moisten the surface and if it dries within 10-15 minutes painting can begin.

THINNER/CLEANER

Water.

APPLICATION METHOD

Brush (recommended) or medium pile roller

CLEANING

Clean all equipment with soapy water immediately after use.

DISPOSAL

Dispose of in accordance with local authority requirements.

Do not allow the product to enter watercourses or drains or where ground or surface waters may be affected.

All waste material including empty containers are controlled wastes and should be disposed of in accordance with the regulations under The Control Of Pollution Act.

SAFETY PRECAUTIONS

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- If medical advice is needed, have product container or label at hand.

| | |
|--------------------------------|--|
| RESPIRATORY PROTECTION: | Wear a dust mask. |
| HAND PROTECTION: | Wear protective gloves. |
| SKIN PROTECTION: | Cover arms and legs. |
| EYE PROTECTION: | Wear suitable safety glasses |
| IF SWALLOWED: | Do not induce vomiting. Seek medical advice if ingested or if an allergic reaction occurs. |

Full Safety Data Sheet available on request.

PRODUCT ASSISTANCE

Contact Earles Paint:

Email: enquiries@earlespaint.co.uk

phone: +44(0)1665 494034

www.earlespaint.co.uk

Important: The content of this documentation is based on our experience of the product. The company guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application including non-use of the company's approved application tools, application by non-competent personnel, use of products not compatible with the company's products or bad weather conditions. For further information, refer to the material safety data sheet.